### MONTANA STATE AVIATION SYSTEM PLAN 1995 UPDATE FIELD INSPECTION FORM

AIRPORT:	SHELBY (SBX)	AIRPORT REFERENCE CODE:	B-II (SM)
CITY:	SHELBY	APPROACH TYPE:	VISUAL
CONTACT:	JERRY LARSON	DATE INVENTORIED:	1-25-96
PHONE #:	434-2462	INSPECTED BY:	RSD

	REQUIRED		ACTUAL		ALP	CONFO	)RM
RUNWAY 11/29 INVENTORY			7.0.07.		, . <u>_</u> .		
DISTANCE TO:							
HOLD LINES FROM CENTERLINE:	125'		128' & 130'			1	
PARALLEL TAXIWAY FROM CENTERLINE:	150'		240' & 291'			/	
AIRCRAFT PARKING FROM CENTERLINE:	125'		300'+			/	
RUNWAY WIDTH:	60'		60'			/	
RUNWAY LENGTH:	4,940' (1)		00		3,700'	75%	
RUNWAY SAFETY AREA (RSA) WIDTH:	120'		OK		0,700	<b>√</b>	
RUNWAY OBJECT FREE AREA (OFA) WIDTH:	250'		OK			/	
PRIMARY / TRANSITION SURFACE PENETRATIONS:	250' W & 7:1		(3)			NO	
LONGITUDINAL GRADE - SITE DIST. PROBLEMS:	200 11 0 7.1		OK			<b>√</b>	
OBSTACLE FREE ZONE ANALYSIS:	250' W x 200' E	REV	_			/	
PAVEMENT EDGE LIP HEIGHT (MIN AND MAX):	1.5" - 3"		FLUSH - 2"			NO (2	2)
PAVEMENT MARKING TYPE:	BASIC		BASIC			110 (2	-)
PAVEMENT MARKING CONDITION:	D/ (OIO		FAIR			N/A	
TAVEINENT MARKING CONDITION.			1 AllX			11//	
RUNWAY 11 END INVENTORY							
SAFETY AREA (RSA) BEYOND RUNWAY END:	240'		OK			✓	
OBJECT FREE AREA (OFA) BEYOND RUNWAY END:	240'		OK			✓	
APPROACH OBSTRUCTIONS:	20:1		NONE			✓	
RUNWAY END ELEVATION:					3,411.2	N/A	
RUNWAY 29 END INVENTORY							
SAFETY AREA (RSA) BEYOND RUNWAY END:	240'		(3)			NO	
OBJECT FREE AREA (OFA) BEYOND RUNWAY END:	240'		OK			140	
APPROACH OBSTRUCTIONS:	20:1		NONE			/	
RUNWAY END ELEVATION:	20.1		INOINL		3,424.1	N/A	
NOWWAT END ELEVATION.					3,424.1	I IV/A	
RUNWAY LIGHTING INVENTORY							
DISTANCE FROM PAVEMENT EDGE:	10'		10'			✓	
MAXIMUM DISTANCE BETWEEN LIGHTS:	200'		OK			✓	
TYPE:	MIRL - BASE M	OU	NTED - ADB ALI	NA	CO & NATIONAL	N/A	
CONDITION:			NEW/GOOD			N/A	
COLOR:	WHITE		WHITE			✓	
THRESHOLD 11							
DISTANCE FROM PAVEMENT EDGE:	10'		10'			/	
MAXIMUM DISTANCE BETWEEN LIGHTS:	10'		10'			/	
COLOR:	RED/GREEN		RED/GREEN			/	
	INED/ONLEN		NED/ONLEN			_	
THRESHOLD 29							
	10'		10'			✓	
MAXIMUM DISTANCE BETWEEN LIGHTS:	10'		10'			<b>✓</b>	
COLOR:	RED/GREEN		RED/GREEN			✓	

# COMMENTS:

- (1) RW LENGTH OF 3,620' FOR 75%, 4,540 FOR 95% AND 4,940 FOR 100% COVERAGE; ALP ULT OF 3,700' SHOWN ON ALP (80% OF PRIMARY RUNWAY LENGTH IS 4,000' DOES NOT CONFORM)
- (2) MOST OF THIS RUNWAY NORTH OF 5/23 IS OK SINCE IT IS A RECENT EXTENSION; SOUTH END EDGES ARE FLUSH
- (3) RISING TERRAIN IN SOUTH CORNER OF RSA; PENETRATES PRIMARY SURFACE

### MONTANA STATE AVIATION SYSTEM PLAN 1995 UPDATE FIELD INSPECTION FORM

AIRPORT:	SHELBY (SBX)	AIRPORT REFERENCE CODE:	B-II (SM)
CITY:	SHELBY	APPROACH TYPE:	NPI
CONTACT:	JERRY LARSON	DATE INVENTORIED:	1-25-96
PHONE #:	434-2462	INSPECTED BY:	RSD

	REQUIRED		ACTUAL		ALP	-	CONFORM
RUNWAY 5/23 INVENTORY						Ī	
DISTANCE TO:							
HOLD LINES FROM CENTERLINE:	125'		128' & 203'				✓
PARALLEL TAXIWAY FROM CENTERLINE:	240'		587.5				/
AIRCRAFT PARKING FROM CENTERLINE:	250'		605'				/
RUNWAY WIDTH:	75'		75'				/
RUNWAY LENGTH:	4,940'				5,000'		/
RUNWAY SAFETY AREA (RSA) WIDTH:	150'		OK		,		✓
RUNWAY OBJECT FREE AREA (OFA) WIDTH:	500'		(1)				NO
PRIMARY / TRANSITION SURFACE PENETRATIONS:	500' W & 7:1		(2) & (3)				NO
LONGITUDINAL GRADE - SITE DIST. PROBLEMS:			`ÓK`				✓
OBSTACLE FREE ZONE ANALYSIS:	250' WIDE x 20	00' B	EYOND				(2) & (3)
PAVEMENT EDGE LIP HEIGHT (MIN AND MAX):	1.5" - 3"	F	FLUSH/1.5"				NO
PAVEMENT MARKING TYPE:	NPI		NPI				OK
PAVEMENT MARKING CONDITION:			FAIR/NEW				N/A
DUNINAN E FAID INIVENTORY							
RUNWAY 5 END INVENTORY	0001		(4)				NO
SAFETY AREA (RSA) BEYOND RUNWAY END:	300'		(4)				NO
OBJECT FREE AREA (OFA) BEYOND RUNWAY END:	300'		(5)				NO
APPROACH OBSTRUCTIONS:	20:1		NONE				<b>√</b>
RUNWAY END ELEVATION:					3,411.7		N/A
RUNWAY 23 END INVENTORY							
SAFETY AREA (RSA) BEYOND RUNWAY END:	300'		OK				✓
OBJECT FREE AREA (OFA) BEYOND RUNWAY END:	300'		OK				✓
APPROACH OBSTRUCTIONS:	20:1		NONE				/
RUNWAY END ELEVATION:	-		_		3438.3		N/A
RUNWAY LIGHTING INVENTORY							
DISTANCE FROM PAVEMENT EDGE:	10'		10'				
MAXIMUM DISTANCE BETWEEN LIGHTS:	-						<i>y</i>
	200'   MIRL - BASE M		OK		14.00		
TYPE: CONDITION:	IVIIRL - BASE IV	VIOU	NEW	\LI\	IACO		N/A
	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\						N/A
COLOR:	WHITE		WHITE				✓
THRESHOLD 5							
DISTANCE FROM PAVEMENT EDGE:	10'		10'				✓
MAXIMUM DISTANCE BETWEEN LIGHTS:	10'		10				✓
COLOR:	RED/GREEN		RED/GREEN				✓
THRESHOLD 23							
DISTANCE FROM PAVEMENT EDGE:	10'		10'				✓
MAXIMUM DISTANCE BETWEEN LIGHTS:	10'		10'				/
COLOR:	RED/GREEN		RED/GREEN				<b>/</b>
OOLON.	INLU/ONLLIN		IVED/OIVEEIN				•

# COMMENTS:

- (1) TWO LARGE ROCKS AND A PIECE OF OLD FARM EQUIPMENT IN OBJECT FREE AREA
- (2) FENCE OUTSIDE OFA PENETRATES TRANS. SURF. 1'-2'; (HAS TO BECAUSE ROAD CAN'T MOVE SOUTH W/O MAJOR EARTHWORK)
- (3) TERRAIN PENETRATES PRIMARY SURFACE, 4' IN WORST AREA,  $\sim$  170' N OF CL, FROM  $\sim\!300'$  E OF STUB TW TO  $\sim\!500'$  W OF TW
- (4) BAD TRANSITION ONTO PAVEMENT EDGE (DIP)
- (5) FENCE IN OBJECT FREE AREA ON EITHER SIDE OF RUNWAY; BUT LOWER THAN THE RUNWAY,

AND IN MOST CASES NOT EVEN VISIBLE FROM THE RUNWAY

#### MONTANA STATE AVIATION SYSTEM PLAN 1995 UPDATE FIELD INSPECTION FORM

AIRPORT:	SHELBY (SBX)	AIRPORT REFERENCE CODE:	B-II (SM)
CITY:	SHELBY	APPROACH TYPE:	NPI
CONTACT:	JERRY LARSON	DATE INVENTORIED:	1-25-96
PHONE #:	434-2462	INSPECTED BY:	RSD

	REQUIRED	ACTUAL		ALP	CONFORM
TAXIWAY INVENTORY					
TAXIWAY WIDTH:	35'	25' - 35' (1)			NO
TAXIWAY SAFETY AREA WIDTH:	79'	OK			✓
TAXIWAY OBJECT FREE AREA WIDTH:	131'	OK			✓
DIST. FROM CENTERLINE TO FIXED OR MOVEABLE OBJ.	65.5'	OK			✓
PAVEMENT EDGE LIP HEIGHT (MIN AND MAX):	1.5" - 3"	FLUSH - 1.5"			NO (2)
PAVEMENT MARKING TYPE:		YELLOW			✓
PAVEMENT MARKING CONDITION:		NEW/FAIR			N/A
TAXIWAY LIGHTING INVENTORY		(3)			
DISTANCE FROM PAVEMENT EDGE:	10'	10'			✓
MAXIMUM DISTANCE BETWEEN LIGHTS:	200'	OK			✓
TYPE:		REFLECTORS	(4)		N/A
CONDITION:		GOOD			N/A
COLOR:	BLUE	BLUE	(4)		OK

MISCELLANEOUS	
MISCELLANEOUS	

TYPE OF BEACON: MOUNTED ON 50' METAL TOWER, SOUTH OF APRON

SIZE OF BEACON: 12"

OTHER LIGHTING AIDS (VASI,PAPI,REIL): 11 & 23 END: MULTI-ELECTRIC PAPI, GOOD COND, 50' OFF PVMT

5 & 29 END: ADB ALNACO PAPI, NEW, 50' OFF PVMT

WINDCONE (CONDITION & COMPLIANCE): SOUTH OF RW INTERSECTION ~500', LIGHTED, 25', POOR COND

SEGMENTED CIRCLE (CONDITION & COMPLIANCE): PLYWOOD PANELS ON METAL FRAMES SEG. CIRCLE IN FAIR COND

WINDCONE (CONDITION & COMPLIANCE):

SEGMENTED CIRCLE (CONDITION & COMPLIANCE):

FENCING: GOOD

SIGNS: (TYPE, CONDITION, PLACEMENT)

NINE LUMACURVE DIRECTIONAL SIGNS

ALL IN GOOD CONDITION AND 15' FROM PAVEMENT EDGE

## COMMENTS:

- (1) 25' TAXIWAY SERVES ONLY THE B-I RUNWAY 11/29; BUT TWO OF THE THREE 30' TAXIWAYS SERVE THE PRIMARY RUNWAY
- (2) ONLY THE TWO TAXIWAYS INDICATED ON THE DRAWING HAVE FLUSH PVMT EDGES, THE OTHERS ARE ACCEPTABLE
- (3) ALL RUNWAY EXITS HAVE PAIRED BLUE LIGHTS MARKING THEM
- (4) OLDER TAXIWAY SECTIONS HAVE THE OLD "COFFEE CAN" STYLE REFLECTIVE TW MARKERS THAT ARE YELLOW IN COLOR